

EU Standard AC EV Charger

Parameter	Name	KP-RHA-AC7K-X	KP-RHA-AC11K-X	KP-RHA-AC21K-X	
Input	Power Supply	1P+N+PE	3P+N+PE	3P+N+PE	
	Input Voltage	230V±1.5%	400V±15%	400V±15%	
	Input Current	32A	3*16A	3*32A	
	Frequency	50/60 Hz	50/60 Hz	50/60 Hz	
Output	Output Voltage	230V±1.5%	400V±15%	400V±15%	
	Maximum Current	32A	3*16A	3*32A	
	Rate Power	7KW	11KW	21KW	
User Interface	Charge Connector	Type 2 cable			
	Cable Length	5 m			
	LEC Indicator	Green/blue/red			
	LCD Display	4.3 inch LCD			
	RFID Reader	MifareISO/IEC14443A			
	Start Mode	Plug&Play/RFID card/App			
	Emergency Stop	Yes			
Communication	LAN	Yes			
	4G	optional			
	Wifi	Yes			
	Bluetooth	Yes			
	OCPP	OCPP 1.6			
Safety	Energy Meter	Yes			
	RCD	6mA DC			
	Ingress Protection	IP54			
	Impact Protection	Ik10			
	Electrical Protection	Over current protection Residual current protection Surge protection Over/Under voltage protection Over/Under Frequency protection Over temperature protection			
	Certification	CE/CB			
	Certification Standard	EN IEC 61851-1:2019, IEC 61851-1:2017, EN 61851-21-2:2018			
	Warranty	1 Years			
	Environment	Installation	Wall-mount / Pole-mount (Optional)		
		Work Temperature	-30 °C~+50 °C		
Work Humidity		5%~95%			
Work Altitude		<2000m			
Package	Product Dimension	350*250*122 mm (H*W*D)			
	Package Dimension	440*400*190 mm (L*W*H)			
	Net Weight	6.5 kg	7.5kg	9.5kg	
	Gross Weight	7.5kg	8.5kg	10.5kg	
	External Package	Carton			